

## Mechanical Valve



### 订购码 / Ordering Code

<div style="border: 1px solid black; padding: 5px; width: 60px; margin: 0 auto;">MSV</div> <p>规格代码 Specification Code 机械阀 Mechanical Valve</p>	<div style="border: 1px solid black; padding: 5px; width: 60px; margin: 0 auto;">86</div> <p>系列代号 Series Code 86系列 / Series 98系列 / Series</p>	<div style="border: 1px solid black; padding: 5px; width: 60px; margin: 0 auto;">32</div> <p>位通数 32: 二位三通 52: 二位五通 Position and Way Number 32: Two-position Three-way 52: Two-position Five-way</p>	<div style="border: 1px solid black; padding: 5px; width: 60px; margin: 0 auto;">1</div> <p>接口口径 Joint Pipe Bore 1: G1/8" 2: G1/4"</p>	<div style="border: 1px solid black; padding: 5px; width: 60px; margin: 0 auto;">R</div> <p>按钮形式 / Button Type 空白: 基本型 / Blank: Basic Type R: 滚轮型 / Roller Type TB: 选择型旋钮 / Selective Knob LB: 加长型旋钮 / Strengthened Knob PB: 大圆型按钮 / Large Round Button PP: 平圆型按钮 / Flat Round Button PPL: 凸圆型按钮 / Convex Round Button EB: 带锁型按钮 / With Lock Button</p>
--	---	---	--	---

### 规格 / Specification

型号 Model	MSV86321	MSV86522	MSV98322
工作介质 Working Medium	经40微米过滤的空气 / 40 Micron Filtered Air		
位通数 Position and Way Number	二位三通 / Two-position Three-way	二位五通 / Two-position Five-way	二位三通 / Two-position Three-way
压力范围 Pressure Range	0~0.8MPa	0~0.8MPa	0~0.8MPa
温度范围 Temperature Range	0~60℃		
有效截面积 Effective Section Area	12mm <sup>2</sup> (CV=0.67)	16mm <sup>2</sup> (CV=0.89)	16mm <sup>2</sup> (CV=0.89)
接管口径 Joint Pipe Bore	G1/8"	G1/4"	G1/4"